



LED Wall Pack

For Exterior General and Security Lighting

Leapfrog Lighting's LED wall packs are designed for exterior wall-mounted, all-weather applications that require long life, no-maintenance and reliable lighting performance. These applications include building security lighting, entrance lighting, industrial perimeters and more.

Features

- Ideal replacement for metal halide and high-pressure sodium fixtures. Lighting module powered by CREE XTE LEDs, providing high electrical efficiency and extended life.
- Industry leading light output and electrical efficiency
- Sealed fixture, dirt and bug free. Does not attract insects.
- cETL certified for USA and Canada
- DLC certified (60W, 80W, 100W)
- Comprehensive 5 year warranty
- Tested per IESNA LM-79 and LM-80

CONSTRUCTION

IP65 waterproof rated, for exterior use. Heavy duty, rust and corrosion-resistant, die-cast aluminum housing with powder-coated black finish.

ELECTRICAL

Available in 90-277VAC and 347-528VAC versions. Optional photocell/sensor is available.

INSTALLATION

Mounts flush to the electrical junction box.

OPTICS

Impact-resistant tempered glass lens provides long-term durability without yellowing and maximizes light output and electrical efficiency.

Specifications

CCT ¹	LM	W	LM/W	SENSOR	VAC	PART
4000K	3400	40	85	N	90-277	1007-W40N-4001
	3400	40	85	Y	90-277	1007-W40P-4002
	3400	40	85	N	347-528	1007-W40N-4003
	3400	40	85	Y	347-528	1007-W40P-4004
5100	60	85	N	90-277	1007-W60N-4001	
	60	85	Y	90-277	1007-W60P-4002	
	60	85	N	347-528	1007-W60N-4003	
	60	85	Y	347-528	1007-W60P-4004	
6800	80	85	N	90-277	1007-W80N-4001	
	80	85	Y	90-277	1007-W80P-4002	
	8500	100	85	N	90-277	1007-W100N-4001
	8500	100	85	Y	90-277	1007-W100P-4002
5000K	3600	40	90	N	90-277	1007-W40N-5001
	3600	40	90	Y	90-277	1007-W40P-5002
	3600	40	90	N	347-528	1007-W40N-5003
	3600	40	90	Y	347-528	1007-W40P-5004
5400	60	90	N	90-277	1007-W60N-5001	
	60	90	Y	90-277	1007-W60P-5002	
	60	90	N	347-528	1007-W60N-5003	
	60	90	Y	347-528	1007-W60P-5004	
7200	80	90	N	90-277	1007-W80N-5001	
	80	90	Y	90-277	1007-W80P-5002	
	9000	100	90	N	90-277	1007-W100N-5001
	9000	100	90	Y	90-277	1007-W100P-5002

GENERAL

Min. lifetime ³	50,000 hours
Weight	5.0 kg
Dimensions (mm)	363W x 195D x 230H
Ambient Temp Range	-30C to +60C


ELECTRICAL

Power factor	> 0.90
--------------	--------

OPTICAL

CRI ²	> 75
Duv ⁴	< 0.006

1. Tolerances as per ANSI C78.377-2008 Nominal CCT categories
2. CRI refers to the "General CRI" described as Ra in CIE 13.3
3. Lifetime as defined by IESNA LM-80
4. Duv values and tolerances as per ANSI C78.377-2008 Nominal CCT, Table 1, page 8



Contact

Head Office
400 March Road
Ottawa ON Canada
K2K 3H4
(613) 270-7879

North America (toll free):
1-800-396-9109

sales@leapfroglighting.com
www.leapfroglighting.com